

QUALITY AIRCRAFT SINCE 1948

TECNAM

North America

P92

ECHO CLASSIC



ADVANTAGES

- Great Value! Low Cost!
- Built to ASTM Standards
- Can be Configured as a Float Plane
- 620 Pound Useful Load

MAIN CHARACTERISTICS / PERFORMANCE

ENGINE		WEIGHTS		SPEED	
Manufacturer	Rotax	Maximum Take-off weight	1320 lbs.	Max. at Sea Level, Gross Weight	113 kts
Model	912ULS/S2	Standard Equipped weight	700 lbs.	Cruise, 75% Power	108 kts
Power	100 hp	Standard Useful Load	620 lbs.	Vne	138 kts
Number of Cylinders	4	Limit Loads	+4/-2g		
		Ultimate Loads	+6/-3g		
PROPELLER		DIMENSION		STALL SPEED	
Manufacturer	Tonini	Wing Span	29.5 ft.	Flaps up, Power off	36 kts
Model	GT	Wing Area	129 sq. ft.	Flaps down, Power off	26 kts
Number of Blades	2	Fuselage Length	21 ft.		
Type	Fixed	Fuselage Height	8.2 ft.	Rate of Climb at Sea Level	1200 ft/m
		Baggage Allowance	44 lbs.	Service Ceiling	14,800 ft.
				Takeoff run over 50 ft. Obstacle	820 ft.
				Landing run over 50 ft. Obstacle	853 ft.
				Demonstrated crosswind	20 kts

P92 ECHO CLASSIC

www.tecnam.net

P92 ECHO CLASSIC



FLIGHT INSTRUMENTS and INDICATORS

Magnetic Compass
Airspeed Indicator - Kts
Altimeter Dual Mode - IN/Mb
Vertical Speed
Bank Indicator
Flap Indicator
Pitot System
Static System
Stabilator Trim Position Indicator

ENGINE INSTRUMENTS

Tachometer
Hour Recorder
Oil Pressure
Oil Temperature
Cylinder Head Temperature
Fuel Pressure
Voltmeter
LH + RH Fuel Quantity

FLIGHT CONTROLS

Hydraulic Toe Brakers
Parking Brake
Electric Flaps
Dual Flight Controls
Steerable Nose Wheel
Stabilator Trim (electrically actuated from stick)
Engine Controls
• Dual Throttle
• Choke
Flight Trim Controls
• Stabilator (electrically actuated from stick)
Fuel Control Selector with on/off
Panel Switches
• Split Master Switch
• Avionics Master
Starter Key

ELECTRICAL SYSTEM

18 Amp. Hour Battery
12 Volt Alternator - 20 Amp.
Switches
• Landing Light
• Strobe Light
• Nav. Light
12 Volt Socket
Circuit Breaker Panel

FUEL SYSTEM

2 Integral Fuel Tanks (24 gal.)
Total Capacity
• Engine Driven Fuel Pump
• Fuel Quick Drains
• Fuel Gascolator

INTERIOR

Pilot and Copilot Seats
• Adjustable Fore and Aft
• Arm Rest
Seat Belts and Shoulder Harness (all seats)
Wall to Wall Carpeting
Map and Storage Pockets
Luggage Compartment

EXTERIOR

Epoxy Corrosion Proofing, all structure
Lockable LH and RH Doors
Rear Window
All Windows Tinted
Tie Down Rings
Main Wheels, 5.00 x 5
Nose Wheel, 4.00 x 6

EXTERIOR LIGHTS

Vertical Tail Strobe
Taxi Light
Nav. Wing Lights with Strobe
Tail Light

POWERPLANT and PROPELLER

Engines - 1 ROTAX 912ULS2 100 HP,
4 Cylinders liquid/air cooled
Integrated Reduction Gear
Dual Ignition System
Dual Throttle Control
Tubular Steel Engine Mount
Propeller - fixed pitch
Propeller Spinner
Fire Sleeve on Fuel and Oil Lines
Air Filter
Oil Filter
Oil and Water Radiators
Thermostatic Oil Valve

PRODUCT SUPPORT / DOCUMENTS

Manufacturers Full 2 Year
Limited Warranty
Pilot Operating Handbook
Maintenance Manual



TECNAM
NORTH AMERICA

11152 Air Park Road
Ashland, VA 23005

[P] 888.359.4682

www.tecnam.net